



## **TEGLA® Double Fit.**

**Versatile Glazing of Artwork with Dual Benefits.**

---

# TEGLA® Double Fit.

## Advantages at a Glance

- Prevention of Newton-Rings (disturbing visual effects due to adhesion on glossy surfaces) by direct glazing
- Improved transparency and high color rendering, despite the double side structure
- Low reflection, no mirror effects
- Compared to single side structured picture framing products, no risk of confusion during glazing of your artwork
- Protection from dust, humidity and environmental influences
- Extremely durable and scratch-resistant glass surface
- Simple and easy cleaning

## Specifications

- Premium float glass
- Double side structuring
- Cut edges, washed and paper interleaved

## Technical Data

### TEGLA® Double Fit

Glass thickness	2 mm (+0.2/-0.3 mm)
Weight	5 kg/m <sup>2</sup>
Gloss value	80 (±15) – European gloss value measured at 20° (acc. DIN EN ISO 2813)
Residual reflection	1 %
Transmission	91 % total transmission (according to ASTM D 1003)
Haze	1 %
UV protection	45 % (300–380 nm)

## Packaging, Transport and Storage

- Standard size available from stock
- Special sizes or packaging on request

Size	Box content (approx. 60 m <sup>2</sup> )
1,600 x 1,020 mm	36 pieces

**TEGLA® Double Fit** is supplied in transport-safe wooden boxes with acid-free paper liners. In order to avoid humidity between the glass panels, the package is wrapped in plastic foil with a desiccant.

After opening the foil, storage under low humidity is required.

## Handling

**TEGLA® Double Fit** is as easy to handle as ordinary float glass.

## Cleaning Recommendation

Cleaning is done with commercial glass cleaners.

Caution. Do not use cleaners containing fluorides or hydroxides.